



THE FILE COPY

HDL-TR-2125

August 1987

SELECTED OCT 0 7 1987

Resonant Level Lifetime in GaAs/AlGaAs Double-Barrier Structures

by Thomas B. Bahder Clyde A. Morrison John D. Bruno



U.S. Army Laboratory Command Harry Diamond Laboratories
Adelphi, MD 20783-1197

Approved for public release; distribution unlimited.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturers' or trade names does not constitute an official indorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

	UNCLASSIFIED	
SECURITY	CLASSIFICATION OF THIS PAGE	•

111	A185	376
	7101	المهيلة إرها العربي

REPORT DOCUMENTATION PAGE								
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	1b. RESTRICTIVE MARKINGS							
2a. SECURITY CLASSIFICATION AUTHORITY	3. DISTRIBUTION/AVAILABILITY OF REPORT							
2b. DECLASSIFICATION / DOWNGRADING SCHEDU	Approved for public release; distribution unlimited.							
4. PERFORMING ORGANIZATION REPORT NUMBE	5. MONITORING ORGANIZATION REPORT NUMBER(S)							
HDL-TR-2125								
6a. NAME OF PERFORMING ORGANIZATION Harry Diamond Laboratories	6b. OFFICE SYMBOL (If applicable) SLCHD-RT-RA	7a. NAME OF MONITORING ORGANIZATION						
6c. ADDRESS (City, State, and ZIP Code)	 	7b. ADDRESS (CH	y, State, and ZIP	Code)				
2800 Powder Mill Road								
Adelphi, MD 20783-1197								
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER						
U.S. Army Laboratory Command	AMSLC	<u> </u>						
8c. ADDRESS (City, State, and ZIP Code) 2800 Powder Mill Road			UNDING NUMBER		THORK HAVE			
Adelphi, MD 20783-1145		PROGRAM ELEMENT NO. 61102A	PROJECT NO. 1L1611- 02AH44	TASK NO.	WORK UNIT ACCESSION NO.			
11. TITLE (Include Security Classification) Resonant Level Lifetime in GaAs/AlGaAs Double-Barrier Structures 12. PERSONAL AUTHOR(S) Thomas B. Bahder, Clyde A. Morrison, John D. Bruno								
13a. TYPE OF REPORT 13b. TIME CO		14. DATE OF REPO August 1987	RT (Year, Month,		GE COUNT 8			
16. SUPPLEMENTARY NOTATION HDL Project: AE1759, AMS Code: 611102H440011								
17. COSATI CODES	18. SUBJECT TERMS (Continue on reverse	e if necessary and	l identify by b	olock number)			
FIELD GROUP SUB-GROUP	Tunneling, GaAs,	AlGaAs, bistability, negative differential resistance, lifetime						
20 12	1							
19. ABSTRACT (Continue on reverse if necessary and identify by block number) The lifetime of the lowest quasi-bound state localized between the barriers of a GaAs/AlGaAs								
double-barrier structure is calculated as a function of barrier and well dimensions. The results are consistent with high-frequency experiments.								
20 DISTRIBUTION / AVAILABILITY OF ABSTRACT	21. ABSTRACT SECURITY CLASSIFICATION							
■ UNCLASSIFIED/UNLIMITED	UNCLASSIFIED 22b TELEPHONE (Include Area Code) 22c. OFFICE SYMBOL							
Thomas B. Bahder	(202) 394-			ID-RT-RA				

Recently there has been considerable interest in GaAs/AlGaAs double-barrier structures. These structures exhibit a number of interesting features, including negative differential resistance (NDR) [1], fast response times [2], and bistability in current-voltage response [3]. For applications purposes, these structures are particularly attractive because of their NDR and fast response times. The regions of NDR in the I-V characteristics are generally associated with the sharp peaks in the transmission coefficient at certain (resonant) energies, and a theory of I-V response based on this assumption was proposed [4].

The experiments of Sollner et al. [2] indicate that there is significant current response to applied fields at frequencies as high as f = 2.5 THz. This suggests that processes responsible for the NDR have characteristic times which are shorter than the period $1/f = 4 \times 10^{-13}$ s. The characteristic times involved in resonant transport are believed to be the lifetimes of the quasi-bound levels between the barriers [5]. At low frequencies, such that $1/f >> \tau$, where τ is the lifetime of the lowest energy quasi-bound state, current response is expected to follow the dc I-V curve. However, at high frequencies, where $1/f << \tau$, one expects negligible resonant response to the applied voltage.

A semiclassical estimate of the lifetime τ has been made by Luryi [6]; however, when compared with experiments [2], his estimate is too large by almost three orders of magnitude. In order to reconcile his predictions with experiment, Luryi proposed a kinematic argument (sequential tunneling) to explain the observed NDR. Recently, Weil and Vinter [7] have

shown that both explanations of the peak in the I-V curves lead to the same prediction for the I-V response. At this point it is not clear whether these two mechanisms are fundamentally distinct.

It is the purpose of this report to show that within a simple effective-mass picture, a quantum mechanical calculation of the resonant level lifetime is consistent with existing experimental observations [2]. Our results can be used to estimate the lifetimes of the resonant levels for a range of aluminum concentrations and barrier and well dimensions.

We solve the one-dimensional effectivemass Schrodinger equation with the doublebarrier potential

$$V(x) \begin{cases} = 0 & 0 < x < a \\ = V & a < x < a + b \\ = 0 & x > a + b \end{cases}$$
 (1)

where V(x) is an even function of x (the growth direction). In the half-space x > 0, we take the even wavefunctions to be

$$\psi(x) \begin{cases} = A \cos(gx) & 0 < x < a \\ = B \exp(g_1 x) & \\ + C \exp(-g_1 x) & a < x < a + b \end{cases}$$

$$= D \exp(igx) \quad x > a + b$$
 (2)

where

$$g_1 = \left[\frac{2m_c}{\hbar^2}V - g^2\right]^{1/2} ,$$

and the wavevectors, g and g_1 , and energy eigenvalues, $E = \pi^2 G^2 / 2m_c$, are complex



Dist A-1 numbers [8]. This wavefunction represents a particle in the well which can tunnel out to the left or right. Matching the wavefunction and its first derivative at x = a and x = a + b gives a system of four homogeneous equations for the constants A, B, C, and D. These equations will have a nontrivial solution if we require the determinant of the coefficient matrix to vanish. For the wavefunctions of equation (2), this condition gives the following equation for the allowed wavevectors:

$$h(z) \frac{\cot(z)}{z} + \frac{h(z)[1 + \exp\{2\delta h(z)\}] + iz[1 - \exp\{2\delta h(z)\}]}{h(z)[1 - \exp\{2\delta h(z)\}] + iz[1 + \exp\{2\delta h(z)\}]} = 0 , (3)$$

where z = ga, $\delta = b/a$, and the dimensionless potential is defined as $U = 2m_c a^2 V/\hbar^2$. The complex function h(z) is chosen such that

$$h(z) = [u - z^2]^{1/2}$$
 $Re(z^2) < U$,
 $h(z) = i[z^2 - U]^{1/2}$ $Re(z^2) > U$,

where the principal branch is taken for the square root. When $Re(z^2) < U$, the resonant level lies below the tops of the barriers; when > U, the resonant level lies above the tops of the barriers. Wavevectors for the odd eigenfunctions satisfy an equation identical to equation (3), but with cot(z) replaced by -tan(z).

The roots of equation (3) are located at z_n , $n = \pm 1, \pm 2, \pm 3, \ldots$, such that $z_n = -z_{-n}^*$. We have numerically solved for these roots as a function of U and δ . All roots have negative imaginary parts [9], and the magnitude of both the real and imaginary parts increases with increasing n. This leads to wavefunctions with a

time dependence given by $\exp(-i\Omega_n t)$ $\exp(-t/2\tau_n)$, where the energy of a resonant level, $\pi\Omega_n$, and the lifetime, τ_n , are functions of the roots z_n :

$$\Omega_n = \omega_0 \operatorname{Re} \left[z_n^2 \right] , \qquad (4)$$

$$\tau_n = \frac{-1}{2\omega_0 \operatorname{Im} \left[z_n^2\right]} , \qquad (5)$$

where ω_0 is defined by

$$\omega_0 = \pi/2m_c a^2 .$$

If we order the roots with positive real parts according to $Re(z_1) < Re(z_2) < Re(z_3) \dots$, the increasing index n labels resonant levels of increasing energy and decreasing lifetime.

In figure 1 we plot the logarithm of the lifetime of the lowest resonant level as a function of δ , for several values of U. The curves are straight lines, which indicates that the lifetime is an exponential function of δ , as one might expect. For a given well width, a, the lifetime increases with both the barrier height and width. In figure 2 we show the energy of the lowest resonant level, $\Re \Omega_1$, as a function of δ . For a given barrier height, the energy has a strong dependence for narrow barriers (values of $\delta \leq 1$). Note also that for a given barrier width, the energy of the resonant state increases with barrier height, which is a simple consequence of electron confinement.

We apply our results to the experiments of Sollner et al. [2], which had the parameter values a = 24 Å, $\delta = 2$, and V = 0.23 eV. Using

the effective mass for conduction electrons in GaAs, $m_c = 0.067 \text{ m}_0$, the frequency scale is ω_0 = 1.38×10^{14} s⁻¹, and U = 2.5 is the dimensionless potential. For these parameter values we find the lifetime of the lowest resonance to be t_1 = 6.4×10^{-13} s. We believe this value for the lifetime is consistent with the high frequency experiments, considering the degree of approximation involved. We have ignored the effects of bias voltage on the potential energy shape and have used the effective mass theory in a rather cavalier manner, ignoring both the mixing of Γ - and X-point states for high aluminum concentration [10] and details of band structure [11]. We believe that a more careful treatment including these effects would not substantially alter our results.




Figure 1. The base 10 logarithm of the product $\omega_{\rm q} \tau$ is plotted versus $\delta = b/a$, where τ is the lifetime of the lowest resonant level ($w\tau_{\rm l}$ in the text).




Figure 2. The energy of the lowest resonant state, $\pi\Omega$ ($\equiv\pi\Omega_1$ in the text), is plotted (in units of $\pi\omega_{\rm e}$) versus δ , for several values of U.

References

- 1. L. Chang, L. Esaki, and T. Tsu, Resonant Tunneling in Semiconductor Double Barriers, Appl. Phys. Lett. 24 (1974), 593.
- T.C.L.G. Sollner, W. D. Goodhur, P. E. Tannenwald, C. D. Parker, and D. D. Peck, Resonant Tunneling Through Quantum Wells at Frequencies up to 2.5 THz, Appl. Phys. Lett. 43 (1983), 588.
- 3. V. J. Goldman, D. C. Tsui, and J. E. Cunningham, Observation of Intrinsic Bi-stability in Resonant-Tunneling Structures, Phys. Rev. Lett. <u>58</u> (1987), 1256.
- 4. R. Tsu and L. Esaki, Tunneling in a Finite Superlattice, Appl. Phys. Lett. 22 (1973), 562.

- 5. B. Ricco and M. Ya. Azbel, *Physics* of Resonant Tunneling. The One-Dimensional Double-Barrier Case, Phys. Rev. B29 (1984), 1970.
- 6. S. Luryi, Frequency Limit of Double-Barrier Resonant-Tunneling Oscillators, Appl. Phys. Lett. 47 (1985), 490.
- 7. T. Weil and B. Vinter, Equivalence Between Resonant Tunneling and Sequential Tunneling in Double-Barrier Diodes, Appl. Phys. Lett. 50 (1987), 1281.
- 8. See, for example, *Quantum Mechanics*, L. D. Landau and E. M. Lifshitz, Pergamon Press, New York (1977), section 134.
- 9. The apparent root when h(z) = 0 of equation (3) is spurious. At this root, $g_1 = 0$ and $g^2 = 2m_c V/h^2$, so the wavefunction in the region 0 < x < a + b is $\psi(x) = Bx + C$. Proceeding as in the derivation of equation (3) gives $\cot(z) (z\delta + i) = 0$, and $z = \sqrt{U}$ is not a solution.
- 10. L. Brey and C. Tejedor, Tunneling of Electrons in Quantum Wells with Indirect Gap Semiconductor Barriers, Solid State Comm. 61 (1987), 573.
- 11. R. Lassnig, Tunneling Through Semiconductor Heterojunction Barriers, Solid State Comm. 61 (1987), 577.

DISTRIBUTION

ADMINISTRATOR
DEFENSE TECHNICAL INFORMATION CENTER
ATTN DTIC-DDA (12 COPIES)
CAMERON STATION, BUILDING 5
ALEXANDRIA, VA 22304-6145

ENGINEERING SOCIETIES LIBRARY ATTN ACQUISITIONS DEPT 345 EAST 47TH STREET NEW YORK, NY 10017

COMMANDER
US ARMY MATERIALS & MECHANICS
RESEARCH CENTER
ATTN DRXMR-TL, TECH LIBRARY BR
WATERTOWN, MA 02172

COMMANDER
US ARMY RESEARCH OFFICE (DURHAM)
PO BOX 12211
ATTN B. D. GUENTHER
ATTN R. J. LONTZ
ATTN C. BOGOSIAN
ATTN M. STROSCIO
RESEARCH TRIANGLE PARK, NC 27709

COMMANDER
US ARMY COMBAT SURVEILLANCE & TARGET
ACQUISITION LABORATORY
ATTN G. IAFRATE
ATTN R. LAREAU

ATTN D. SMITH ATTN L. YERKE ATTN T. AUCOIN

FT MONMOUTH, NJ 07703

DIRECTOR
NAVAL RESEARCH LABORATORY
ATTN CODE 2620, TECH LIBRARY BR
ATTN A. M. KRIMAN
WASHINGTON, DC 20375

THE AEROSPACE CORPORATION ATTN FRANK VERNON ATTN RICHARD KRANTZ P.O. BOX 92957 LOS ANGELES, CA 90009

AT&T BELL LABORATORIES
ATTN B. A. WILSON
ATTN A. Y. CHO
ATTN S. LURYI
ATTN J. E. CUNNINGHAM
ATTN W. T. TSANG
600 MOUNTAIN AVE
MURRAY HILL, NJ 07974

BERKELEY RESEARCH ASSOCIATES, INC PO BOX 852 ATTN R. D. TAYLOR SPRINGFIELD, VA 22150

DIRECTOR
ADVISORY GROUP ON ELECTRON DEVICES
ATTN SECTRY, WORKING GROUP D
201 VARICK STREET
NEW YORK, NY 10013

GOVERNMENT SYS. DIV RCA MS 108-102 ATTN S. KATZ MOORESTOWN, NJ 08057

HONEYWELL PHYSICAL SCIENCES CTR ATTN P. P. RUDIN 10701 LYNDALE AVENUE SOUTH BLOOMINGTON, MN 55420

IBM
T. J. WATSON RESEARCH CENTER
ATTN P. J. PRICE
ATTN L. L. CHANG
ATTN L. ESAKI
ATTN C. E. T. GONCALVES
ATTN E. E. MENDEZ
ATTN W. J. WANG
YORKTOWN HEIGHTS, NY 10598

LINCOLN LABORATORIES
ATTN E. R. BROWN
ATTN T. C. L. G. SOLLNER
ATTN W. D. GOODHUE
ATTN C. D. PARKER
MASSACHUSETTS INSTITUTE OF
TECHNOLOGY
LEXINGTON, MA 02173

MARTIN MARIETTA
ATTN F. CROWNE
ATTN R. LEAVITT
ATTN J. LITTLE
ATTN T. WORCHESKY
1450 SOUTH ROLLING ROAD
BALTIMORE, MD 21226

SCIENTIFIC APPLICATIONS, INC. ATTN B. GORDON 3 DOWNING RD HANOVER, NH 03755

TEXAS INSTRUMENTS ATTN W. R. FRENSLEY ATTN M.A. REED

DISTRIBUTION (cont'd)

TEXAS INSTRUMENTS (cont'd) ATTN J. W. LEE ATTN H-L. TSAI CENTRAL RESEARCH LABORATORY DALLAS, TX 76265

XEROX CORPORATION ATTN R. D. BURNHAM ATTN F. A. PONCE PALO ALTO, CA 94304

CALIFORNIA INSTITUTE OF TECHNOLOGY ATTN A. R. BONNEFOI ATTN R. T. COLLINS ATTN T. C. McGILL PASADENA, CA 91125

UNIVERSITY OF CALIFORNIA LOS ANGELES ATTN B. JOGAI ATTN K. L. WANG DEPT. OF ELEC. ENG. LOS ANGELES. CA 90024

UNIVERSITY OF HAWAII DEPT OF PHYSICS ATTN C. VAUSE 2505 CORREA RD HONOLULU, HI 96822

UNIVERSITY OF MARYLAND DEPT OF ELEC. ENG. ATTN C. H. LEE COLLEGE PARK, MD 20742

NORTH CAROLINA STATE
UNIVERSITY
ATTN G. S. LEE
ATTN K. Y. HSIEH
ATTN R. M. KOLBAS
DEPT. OF ELEC. ENG.
RALEIGH, NC 27695

PENN STATE UNIVERSITY DEPT OF PHYSICS ATTN M. R. GIRI HAZLETON, PA 18201

PRINCETON UNIVERSITY ATTN V. J. GOLDMAN ATTN D. C. TSUI DEPT. OF ELEC. ENG. PRINCETON, NJ 08544

US ARMY LABORATORY COMMAND ATTN TECHNICAL DIRECTOR, AMSLC-TD ATTN PUBLIC AFFAIRS, AMSLC-PA INSTALLATION SUPPORT ACTIVITY
ATTN LIBRARY, SLCIS-IM-TL (3 COPIES)
ATTN LIBRARY, SLCIS-IM-TL (WOODBRIDGE)
ATTN LEGAL OFFICE, SLCIS-CC

USAISC
ATTN RECORD COPY, ASNC-ADL-TS
ATTN TECHNICAL REPORTS BRANCH,
ASNC-ADL-TS (2 COPIES)

HARRY DIAMOND LABORATORIES ATTN D/DIVISION DIRECTORS ATTN CHIEF, SLCHD-NW-E ATTN CHIEF, SLCHD-NW-EC ATTN CHIEF, SLCHD-NW-ED ATTN CHIEF, SLCHD-NW-EE ATTN CHIEF, SLCHD-NW R ATTN CHIEF, SLCHD-NW-RA ATTN CHIEF, SLCHD-NW-RC ATTN CHIEF, SLCHD-NW-RE ATTN CHIEF, SLCHD-NW-RH ATTN CHIEF, SLCHD-NW-RI ATTN CHIEF, SLCHD-NW-P ATTN CHIEF, SLCHD-RT-RA ATTN CHIEF, SLCHD-RT-RB ATTN A. HARMANN, SLCHD-NW-EC ATTN C. S. KENYON, SLCHD-NW-EC ATTN D. TROXEL, SLCHD-NW-EC ATTN F. B. MCLEAN, SLCHD-NW-RC ATTN P. BRODY, SLCHD-RT-RA ATTN J. BRUNO, SLCHD-RT-RA (20 COPIES) ATTN H. DROPKIN, SLCHD-RT-RA ATTN E. EDWARDS, SLCHD-RT-RA ATTN K. HALL, SLCHD-RT-RA ATTN M. HANSEN, SLCHD-RT-RA ATTN G. HAY, SLCHD-RT-RA ATTN E. KATZEN, SLCHD-RT-RA ATTN C. MORRISON, SLCHD-RT-RA (10 COPIES) ATTN R. NEIFELD, SLCHD-RT-RA ATTN C. PENNISE, SLCHD-RT-RA ATTN R. SCHMALBACH, SLCHD-RT-RA ATTN A. SEMENDY, SLCHD-RT-RA ATTN G. SIMONIS, SLCHD-RT-RA ATTN T. SIMPSON, SLCHD-RT-RA ATTN M. STEAD, SLCHD-RT-RA ATTN J. STELLATO, SLCHD-RT-RA ATTN M. TOBIN, SLCHD-RT-RA ATTN G. TURNER, SLCHD-RT-RA ATTN D. WORTMAN, SLCHD-RT-RA ATTN R. FELOCK, SLCHD-RT-RB ATTN C. GARVIN, SLCHD-RT-RB ATTN J. GOFF, SLCHD-RT-RB ATTN N. KARAYIANIS, SLCHD-RT-RB ATTN D. McGUIRE, SLCHD-RT-RB ATTN P. PELLEGRINO, SLCHD-RT-RB

ATTN T. BAHDER, SLCHD-RT-RA (20 COPIES)